

EAST: (10749810 conformal conductive between lid and chips.wsp.f)

File View Edit Tools Window Help

Drafts

- BRS:
- BRS:
- BRS:
- BRS: knall
- BRS: 19 2129
- BRS: 32 with 33
- BRS:
- BRS: \$4

Pending

Active

- L1: (1010252) cavity concave
- L2: (1456788) chip ic die
- L3: (20071) (per one) adj L1
- L4: (14547) two nd) L2
- L5: (177) L3 with L4

Failed

Saved

- S1: (11) 09/948877
- S2: (1738) "KONINKLIKE PHILIPS".as.
- S3: (14) Single adj electron adj resistor adj memory
- S4: (1408837) channel
- S5: (13) (Single adj electron adj resistor adj memory) and channel
- S6: (0) 10/698514
- S7: (0) 10/7498107
- CR: (198771) 111

US PATENT DOCUMENT 64 700

US 200200

L3 with L4

Apr 2005

U	I	Inventor	Document	Issued	P	Title	Current	Current	X	Retrieval	S	C	P	Image	De	P
1		Brooks, John	US 200200	2002	15	Terminal block with shoulder contact	439/70								US 20020	
2		Matsumoto	US 200200	2002	12	Semiconductor device and method of	438/45								US 20020	
3		Matsumoto	US 666462	2003	13	Semiconductor device and method of	257/771	257/222							US 66646	
4		Krueger, David	US 510005	1992	8	Method of manufacturing dual alloy tu	228/26	228/193							US 510005	
5		Hadaway, B	US 4928375	1990	9	Method of forming a hollow fastener fr	29/509	192/1870							US 492837	
6		Jones, W. K.	US 4614194	1986	11	Implantable pulse generator having a	607/2	257/734							US 461419	
7		Kreutzner, A	US 4383672	1983	4	Mold tooling for the manufacture of th	249/13	249/102							US 438367	
8		Biaszkowski	US 4279854	1981	6	Method and apparatus for forming sea	264/27	249/83							US 427985	
9		Bourset, G.	US 4211384	1980	7	Molding assembly for casting soft cont	249/16	425/808							US 421138	
10		Maitenaz, B	US 4018587	1977	5	Method for producing a curved glass di	264/27	264/25							US 401858	

US PATENT DOCUMENT 64 700

US 200200

US 666462